



### Compression Tools

	VT-100 Not sold anymore	VT150DK	VT-200	VT-300	VTCMP11	CT2-AS (CAT-AS)	CT2-AS-EX (CAT-AS-EX)	EX59/6 CATU	EX59/6CAT	CAT- MULTIMEDIA- PPC	CAT-AS IEC/F-FX	CATAIO PLUNGER 1 & 2	CATAIO2 PLUNGER 1 & 7	PLUNGERS for CATAIO
EX XL F connector: -EX6/59XL -EX59XLHE -EX6XLP	●	●	●			●		●		●	●	●	●	IPT 1A
EX F Connector: -EX6/59 -EX59HE -EX6P		●		●			●	●				●		IPT 2A
EX 7/11/320 -ALL MODELS			●	●		●	●				●	●	●	IPT 1B
EX XL AQUATIGHT: -EX6XLWS -EX59XLWS		●	●			●					●	●	●	IPT 1A
EX AQUATIGHT: -EX6WS -EX6-51WS -EX59WS				●			●					●		IPT 2A
EX BNC: -EXBNC6 -EXBNCHE -EXBNC9167										●			●	IPT 7 ONLY IN CATAIO2
EX-IEC -EX6-49/83-IECm -EX6-49/83-IECf -EX6-51/83-IECm -EX6-51/83-IECf -EX59-39/79-IECm -EX59-39/79-IECf		●									●	●	●	IPT 1A
EX Evertight: -EX59XLET -EX6XLET		●	●			●		●		●	●	●	●	IPT 1A
EX Plus: -EX59XLPLUS -EX6XLPLUS		●	●			●		●		●	●	●	●	IPT 1A
CMP F Connector: -CMP59/59Q -CMP6/6Q	●	●	●			●		●		●	●	●	●	IPT 1A
CMPMC CMPMCWS		●		●			●	●				●		IPT 2A
CMP BNC -CMPBNC6/59 -CMPBNC59HE -CMPBNC-MINI										●			●	IPT 7 ONLY IN CATAIO2
CMP RCA -CMPRCA6/59 -CMPRCA-MINI										●	●	●	●	IPT 1A
CMP11 58m - 58ms Fm - 3512m - IECm					●									
CMP IEC -CMPIEC6/59 -CMPIECMC		●									●	●	●	IPT 1A
CMP WS "AquaTight"		●	●								●	●	●	IPT 1A

Cable Preparation Tools		Drop Cable Types		Replacement Cassettes	
	Lightweight Drop Trimmer is used for preparation of the cable, before putting on the connector. Removes the jacket and exposes the center conductor in the proper length and without damaging the cable.				
	LDT596-250	RG 59, RG 6 and Beta Cavi N48		RC596-250 RED	
	LDTMINI	3.7 mm MINI and Beta Cavi N35		RCMINI-250 WHITE	
	Dual Drop Trimmer is used for preparation of the cable, before putting on the connector. Removes the jacket and exposes the center conductor in the proper length and without damaging the cable (Beta Cavi=BC)				
	DDT59611	RG 59, RG 6, N48, RG 11		RC596-250 RED & RC11-250 BLACK	
	DDT596MINI	RG 59, RG 6, N48, 3.7 mm MINI & BC N38		RC596-250 RED & RC MINI-250 WHITE	
	DDT EURO/11	For RG 59, RG 6, N48, Coax 9 & Coax 11		RCEUR-250 ORANGE & RC11-250 BLACK	
	DDT EUROmini	RG 59, RG 6, N48, Coax 9, 3.7 mm MINI & BC N35		RCEUR-250 ORANGE & RC MINI-250 WHITE	
	Single Drop Trimmer is used for preparation of the cable, before putting on the connector. Removes the jacket and exposes the center conductor in the proper length and without damaging the cable. *Supplied with 11 BLACK, cassette for use on 11 standard and tri shield cable and 11Q GREY cassette for use on 11 Quad shield cable				
	SDT596-250	RG 59, RG 6, Std. Tri & Quad, N48		RC596-250, RED	
	SDT7-250	RG 7 Std. Tri & Quad		RC7-250, GREEN	
	SDT11-250*	RG 11, Std. Tri & Quad		RC11-250 & RC11Q-250, BLACK & GREY	
	Universal Drop Trimmer is used for preparation of the cable, before putting on the connector. Removes the jacket and exposes the center conductor in the proper length and without damaging the cable.(with extra storage compartment) (Beta Cavi=BC)				
	UDT711-250	RG 7, RG 11, RG 11Q		RC11-250 BLACK & RC7-250 GREEN (RC7-250 GREEN, RC11Q-250 GREY in storage compartment)	
	UDT596711-250	RG 59, RG 6, RG 7, RG 11, BC N48		RC596-250 RED, RC11-250 BLACK & (RC7-250 GREEN, RC596-250 RED in storage compartment)	
Installation Tools					
	PST Locking Terminator Tools: Available in two convenient lengths. Longer and larger diameter on LTT-7 (1-1/4 inch/31.8mm diameter) for better grip and leverage. Smaller diameter handle on LTT-4 (1 inch/25.4 mm diameter) provides easier access between trap shields on tap banks.				
	LTT4	4-1/2 inches (114 mm), 1,9 oz. (54 gram)			
	LTT7	8 inches (203 mm), 4,2 oz (118 gram)			
	Torque Wrenches : All wrenches size 7/16 inches ( 11,1 mm) Use to ensure proper connectorization on F connector interfaces, thereby preventing damage to equipment during the tightening. Audible 'clicking' sound to indicate proper calibrated torque is reached.				
	TW 207	Torque in inchpounds 20, torque in newton meters 2.26			
	TW 307	Torque in inchpounds 30, torque in newton meters 3.39			
	TW 307AH	Angled Head model, Torque in inchpounds 30, torque in newton meters 3.39			
	TW307AH-IT	Angle Head Model with Insertion Tool, Torque in inchpounds 30, torque in newton meters 3.39			
	TW307AH-B	Angle Head Basic, Torque in inchpounds 30, torque in newton meters 3.39			
	Security Shield Tool S-200: For use with 7/16 inch hex security shielded F connectors.				
	S-200	Length: 2.75 in (70 mm) & Weight: 2.0 oz (57 gram)			